

Huawei eKitEngine AP673 Wireless Access Point Datasheet



BE14000 Tri-Band Wi-Fi 7 Settled AP

Make SME Network Easier and Smarter



Product Overview

Huawei eKitEngine AP673 is a next-generation indoor access point (AP) that complies with the Wi-Fi 7 (802.11be) standard. It supports eight spatial streams on the 2.4 GHz (2x2 MIMO), 5 GHz (2x2 MIMO), and 6 GHz (4x4 MIMO) frequency bands, delivering a data rate of up to 13.66 Gbps.

It has built-in smart antennas, ensuring always-on signals for users. With the all-new Wi-Fi 7 technology, this AP can greatly improve users' wireless network experience. Compact in size, it can be flexibly deployed and saves customer TCO. These strengths make this AP ideal for indoor coverage scenarios such as small and midsize enterprise office, hospitals, and shopping malls and supermarkets.

You can use the EasyWeb or wireless access controller (WAC) to locally deploy and manage APs, or use the HUAWEI eKit App & SNC platform to remotely manage and maintain APs. In this way, network projects can be handed over or managed together, simplifying network O&M.

Feature Description

Wi-Fi 7 (802.11be) Standard

Wi-Fi 7 (802.11be) — also known as IEEE 802.11be Extremely High Throughput (EHT) — is the latest upcoming Wi-Fi standard. Based on Wi-Fi 6, Wi-Fi 7 introduces technologies such as 320 MHz bandwidth, 4096-quadrature amplitude modulation (4096-QAM), multiple resource unit (MRU), multi-link operation (MLO), enhanced multi-user multiple-input multiple-output (MU-MIMO), and multi-AP coordination. In this way, Wi-Fi 7 delivers a higher data transmission rate and a lower latency than Wi-Fi 6.

High-Speed Tri-Band Access

• The AP supports 320 MHz frequency bandwidth on the 6 GHz frequency band, which increases the number of available data subcarriers and expands transmission channels. In addition, the AP adopts 4096-QAM and MU-MIMO to achieve a rate of up to 0.69 Gbps on the 2.4 GHz band, 1.44 Gbps on the 5 GHz band, and 11.53 Gbps on the 6 GHz band, meaning up to 13.66 Gbps for the device.

Smart Antenna

The dual-band smart antenna array technology and intelligent switchover algorithm enable the AP to
intelligently sense the application environment and access density, achieving accurate Wi-Fi coverage and
interference suppression. They together provide the optimal coverage direction and signal quality for each
access station (STA), and offer seamless and smooth wireless network experience to users.

Wi-Fi 7 vs. Wi-Fi 6

Based on Wi-Fi 6, Wi-Fi 7 introduces many new technologies.



• In the figure, the maximum transmission rate refers to the one of a single radio, for example, 5 GHz radio for Wi-Fi 6 and 6 GHz radio for Wi-Fi 7.

New Features of Wi-Fi 7

Wi-Fi 7 aims to further increase the WLAN throughput to more than 30 Gbps and provide low-latency access assurance. To achieve this goal, the standard defines modifications to both the physical layer (PHY) and MAC layer. Compared with Wi-Fi 6, Wi-Fi 7 brings the following technical innovations:

MRU*

In Wi-Fi 6, each user can send or receive frames only on the RUs allocated to them, which greatly limits the flexibility of spectrum resource scheduling. To resolve this issue and further improve spectral efficiency, Wi-Fi 7 defines a mechanism for allocating multiple RUs to a single user. To balance the implementation complexity and spectrum utilization, the standard specifications impose certain restrictions on RU combination. That is, small RUs (containing fewer than 242 tones) can be combined only with small RUs, and large RUs (containing greater than or equal to 242 tones) can be combined only with large RUs. Small RUs and large RUs cannot be combined together.

• Features marked with the asterisk (*) can be implemented through software upgrade.

Higher-order 4096-QAM

• The highest order modulation supported by Wi-Fi 6 is 1024-QAM, which allows each modulation symbol to carry up to 10 bits. To further improve the rate, Wi-Fi 7 introduces 4096-QAM so that each modulation symbol can carry 12 bits. With the same coding scheme, 4096-QAM in Wi-Fi 7 can achieve a 20% rate increase compared with 1024-QAM in Wi-Fi 6.

Multi-link mechanism

 To efficiently utilize all available spectrum resources, the IEEE 802.11 working group defines technologies related to multi-link aggregation, including the MAC architecture of enhanced multi-link aggregation, multilink channel access, and multi-link transmission.

Multi-AP coordination*

In the current 802.11 protocol framework, there is not much coordination between APs. Common WLAN functions, such as automatic radio calibration and smart roaming, are vendor-defined features. Multi-AP coordination aims to optimize channel selection and adjust loads among APs to achieve efficient utilization and balanced allocation of radio resources. Coordinated scheduling between multiple APs in Wi-Fi 7 involves inter-cell coordinated planning in the time and frequency domains, inter-cell interference coordination, and distributed MIMO. This reduces interference between APs and greatly improves the utilization of air interface resources. There are many coordinated scheduling methods between multiple APs, including coordinated orthogonal frequency-division multiple access (C-OFDMA), coordinated spatial reuse (CSR), coordinated beamforming (CBF), and joint transmission (JXT).

Product Features

Fit AP Mode

Item	Description		
WLAN features	Compliance with IEEE 802.11be and compatibility with IEEE 802.11a/b/g/n/ac/ax		
	Maximum ratio combining (MRC)		
	Space time block code (STBC)		
	Cyclic delay diversity (CDD)/Cyclic shift diversity (CSD)		

Item	Description			
	Beamforming			
	MU-MIMO			
	OFDMA			
	Compliance with 4096-QAM and compatibility with 1024-QAM/256-QAM/64-QAM/16-QAM/8- QAM/QPSK/BPSK			
	Low-density parity-check (LDPC)			
	Frame aggregation, including A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx)			
	802.11 dynamic frequency selection (DFS)			
	Short guard interval (GI) in 20 MHz, 40 MHz, 80 MHz, and 160 MHz modes			
	Wi-Fi Multimedia (WMM) for priority-based data processing and forwarding			
	WLAN channel management and channel rate adjustment			
	Automatic channel scanning and interference avoidance			
	NOTE			
	For detailed management channels, see Country Code & Channel Compliance Table.			
	Separate service set identifier (SSID) hiding configuration for each AP, supporting Chinese SSIDs			
	Unscheduled automatic power save delivery (U-APSD)			
	Control and provisioning of wireless access points (CAPWAP) in Fit AP mode			
	Extended service set (ESS) in Fit AP mode			
	Multi-user CAC			
	802.11k and 802.11v smart roaming			
	802.11r fast roaming			
Network	Compliance with IEEE 202 2ab			
features	Auto-negotiation of the rate and duplex mode			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN Access control list (ACL)			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN Access control list (ACL) Link layer discovery protocol (LLDP)			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN Access control list (ACL) Link layer discovery protocol (LLDP) Uninterrupted service forwarding upon CAPWAP tunnel disconnection in Fit AP mode			
features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN Access control list (ACL) Link layer discovery protocol (LLDP) Uninterrupted service forwarding upon CAPWAP tunnel disconnection in Fit AP mode Unified authentication on the WAC in Fit AP mode			
features	Compliance with IEEE 802.380Auto-negotiation of the rate and duplex modeSSID-based VLAN assignmentManagement channel of the AP's uplink port in tagged or untagged modeDHCP client, obtaining IP addresses through DHCPTunnel data forwarding and direct data forwardingMesh backhaulIPv6HotSpot2.0STA isolation in the same VLANAccess control list (ACL)Link layer discovery protocol (LLDP)Uninterrupted service forwarding upon CAPWAP tunnel disconnection in Fit AP modeUnified authentication on the WAC in Fit AP modeTelemetry in Fit AP mode, quickly collecting AP status and application experience parameters			
features QoS features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN Access control list (ACL) Link layer discovery protocol (LLDP) Uninterrupted service forwarding upon CAPWAP tunnel disconnection in Fit AP mode Unified authentication on the WAC in Fit AP mode Telemetry in Fit AP mode, quickly collecting AP status and application experience parameters WMM power saving			
features QoS features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN Access control list (ACL) Link layer discovery protocol (LLDP) Uninterrupted service forwarding upon CAPWAP tunnel disconnection in Fit AP mode Unified authentication on the WAC in Fit AP mode Telemetry in Fit AP mode, quickly collecting AP status and application experience parameters WMM power saving Priority mapping for uplink packets; flow-based mapping for downlink packets			
features QoS features	Computative with LEL 302.3ab Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN Access control list (ACL) Link layer discovery protocol (LLDP) Unified authentication on the WAC in Fit AP mode Telemetry in Fit AP mode, quickly collecting AP status and application experience parameters WMM power saving Priority mapping for uplink packets; flow-based mapping for downlink packets Queue mapping and scheduling			
features QoS features	Computation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN Access control list (ACL) Link layer discovery protocol (LLDP) Uninterrupted service forwarding upon CAPWAP tunnel disconnection in Fit AP mode Unified authentication on the WAC in Fit AP mode Telemetry in Fit AP mode, quickly collecting AP status and application experience parameters WMM power saving Priority mapping for uplink packets; flow-based mapping for downlink packets Queue mapping and scheduling User-based bandwidth limiting			
features QoS features	Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment Management channel of the AP's uplink port in tagged or untagged mode DHCP client, obtaining IP addresses through DHCP Tunnel data forwarding and direct data forwarding Mesh backhaul IPv6 HotSpot2.0 STA isolation in the same VLAN Access control list (ACL) Link layer discovery protocol (LLDP) Uninterrupted service forwarding upon CAPWAP tunnel disconnection in Fit AP mode Unified authentication on the WAC in Fit AP mode Telemetry in Fit AP mode, quickly collecting AP status and application experience parameters WMM power saving Priority mapping for uplink packets; flow-based mapping for downlink packets Queue mapping and scheduling User-based bandwidth limiting Adaptive bandwidth management (automatic bandwidth adjustment based on the user quantity			

Item	Description		
	Airtime scheduling		
Security	Open system authentication		
features	WPA2-PSK authentication and encryption (WPA2-Personal)		
	WPA2-802.1X authentication and encryption (WPA2-Enterprise)		
	WPA3-SAE authentication and encryption (WPA3-Personal)		
	WPA3-802.1X authentication and encryption (WPA3-Enterprise)		
	WPA-WPA2/WPA2-WPA3 hybrid authentication		
	WPA2-PPSK authentication and encryption in Fit AP mode		
	Wireless intrusion detection system (WIDS) and wireless intrusion prevention system (WIPS)		
	802.1X authentication, MAC address authentication, Portal authentication, etc.		
	DHCP snooping		
	802.11w Protected Management Frames (PMF)		
802.11w Protected Management Frames (PMF)			
	DTLS encryption		
	Dynamic ARP inspection (DAI)		
	IP Source Guard (IPSG)		
Maintenance	Unified management and maintenance on the WAC in Fit AP mode		
features	Automatic login, automatic configuration loading, and plug-and-play (PnP) in Fit AP mode		
	Automatic batch upgrade in Fit AP mode		
	STelnet using SSHv2		
	SFTP using SSHv2		
	Real-time configuration monitoring and fast fault locating using the network management system		
	(NMS)		
	System status alarm		

Cloud Management Mode/FAT AP Mode

ltem	Description		
WLAN features	Compliance with IEEE 802.11be and compatibility with IEEE 802.11a/b/g/n/ac/ax		
	Maximum ratio combining (MRC)		
	Space time block code (STBC)		
	Cyclic delay diversity (CDD)/Cyclic shift diversity (CSD)		
	Beamforming		
	MU-MIMO		
	OFDMA		
	Compliance with 4096-QAM and compatibility with 1024-QAM/256-QAM/64-QAM/16-QAM/8- QAM/QPSK/BPSK		
	LDPC		
	Frame aggregation, including A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx)		
	802.11 DFS		
	Short GI in 20 MHz, 40 MHz, 80 MHz, 160MHz and 320 MHz modes		
	NOTE		
	320MHz need to support 6GHz.		

ltem	Description
	WMM for priority-based data processing and forwarding WLAN channel management and channel rate adjustment NOTE For detailed management channels, see <i>Country Code & Channel Compliance Table</i> .
	Automatic channel scanning and interference avoidance SSID hiding configuration for each AP, supporting Chinese SSIDs U-APSD
	802.11k and 802.11v smart roaming 802.11r fast roaming
Network features	Compliance with IEEE 802.3ab Auto-negotiation of the rate and duplex mode SSID-based VLAN assignment DHCP client, obtaining IP addresses through DHCP STA isolation in the same VLAN ACL Unified authentication on the cloud management platform Mesh backhaul IPv6 HotSpot2.0
QoS features	 WMM power saving Priority mapping for uplink packets; flow-based mapping for downlink packets Queue mapping and scheduling User-based bandwidth limiting Adaptive bandwidth management (automatic bandwidth adjustment based on the user quantity and radio environment) for user experience improvement Airtime scheduling
Security features	Open system authentication WPA2-PSK authentication and encryption (WPA2-Personal) WPA2-802.1X authentication and encryption (WPA2-Enterprise) WPA3-SAE authentication and encryption (WPA3-Personal) WPA3-802.1X authentication and encryption (WPA3-Enterprise) WPA-WPA2/WPA2-WPA3 hybrid authentication WPA2-PPSK authentication and encryption Wireless intrusion detection system (WIDS) and wireless intrusion prevention system (WIPS) 802.1X authentication, MAC address authentication, Portal authentication, etc. DHCP snooping DAI IPSG
Maintenance features	Unified management and maintenance on the cloud management platform Automatic AP onboarding and PnP Batch upgrade STelnet using SSHv2

Item	Description	
	SFTP using SSHv2	
Real-time configuration monitoring and fast fault locating using the NMS		
	System status alarm	
	Network Time Protocol (NTP)	

Product Specifications

Item		Description	
Technical specifications	Dimensions (diameter x height)	Φ220 mm x 45 mm	
	Port	1 x 100M/GE/2.5GE/5GE electrical port	
		1 x 10M/100M/GE electrical port	
		1 x USB port	
		NOTE The 5GE electrical port supports PoE IN.	
	LED indicator	Indicate the power-on, startup, running, alarm, and fault states of the system.	
Power	Power input	• DC: 12 V ± 10%	
specifications		 PoE power supply: in compliance with IEEE 802.3at/af 	
		NOTE	
		functions. For example, the USB port is unavailable. For details, see the Quick Information Check website.	
	Maximum power	• 21.1 W (excluding USB)	
	consumption	NOTE	
		The actual maximum power consumption depends on local laws and regulations.	
Environmental	Operating temperature	–10°C to +50°C	
specifications		NOTE	
		temperature upper limit. The AP's performance will not be affected as long as the shell temperature complies with the safety standards.	
	Storage temperature	-40°C to +70°C	
	Operating humidity	5% to 95% (non-condensing)	
	Altitude	–60 m to +5000 m	
	Atmospheric pressure	53 kPa to 106 kPa	
Radio specifications	Antenna type	Built-in smart antennas	
	Antenna gain	2.4 GHz: 4 dBi	
		5 GHz: 5 dBi	
		6 GHz: 5 dBi	

Item		Description	
		NOTE The preceding gains are the peak gains of a single antenna.	
	Maximum quantity of SSIDs on each radio	10	
	Maximum number of access STAs	1024	
	Maximum transmit	2.4 GHz: 23 dBm (combined power)	
	power	5 GHz: 23 dBm (combined power)	
		6 GHz: 26 dBm (combined power)	
		NOTE	
		The actual transmit power varies according to local laws and regulations.	
	Frequency bands	2.400 to 2.4835 GHz ISM	
		5.150 to 5.250 GHz U-NII-1	
		5.250 to 5.350 GHz U-NII-2A	
		5.470 to 5.725 GHz U-NII-2C	
		5.725 to 5.850 GHz U-NII-3/ISM	
		5.925 to 6.425 GHz U-NII-5	
		6.425 to 6.525 GHz U-NII-6	
		6.525 to 6.875 GHz U-NII-7	
		6.875 to 7.125 GHz U-NII-8	
		NOTE	
		The available bands and channels are dependent on the configured regulatory domain (country).	

Standards Compliance

Safety standards		 UL 62368-1 EN 62368-1 IEC 62368-1 CSA 62368-1 	• GB 4943.1
Radio standards	• ETSI EN 300 328	• ETSI EN 301 893	• AS/NZS 4268
EMC	• FN 201 490 1	• CD 0254	
standards	• EN 301 489-1	• GB 9254	• IEC/EN 61000-4-2
standards	• EN 301 489-17	• GB 17625.1	 IEC/EN 61000-4-3
	• EN 60601-1-1	• GB 17625.2	• IEC/EN 61000-4-4
	• EN 60601-1-2	 AS/NZS CISPR 32 	 IEC/EN 61000-4-5
	• EN 55024	• CISPR 24	 IEC/EN 61000-4-6
	• EN 55032	CISPR 32	• ICES-003
	• EN 55035	• CISPR 35	

IEEE standards	 IEEE 802.11a/b/g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11be 	 IEEE 802.11h IEEE 802.11d IEEE 802.11e IEEE 802.11k 	 IEEE 802.11v IEEE 802.11w IEEE 802.11r
Security standards	 802.11i, Wi-Fi Protected Access (WPA), WPA2, WPA2-Enterprise, WPA2-PSK, WPA3, WAPI 802.1X Advanced Encryption Standards (AES), Temporal Key Integrity Protocol (TKIP), WEP, Open EAP Type(s) 		
EMF standards	• EN 62311	• EN 50385	
RoHS standards	 Directive 2002/95/EC & 2011/65/EU (EU) 2015/863 		
Reach standards	 Regulation 1907/2006/EC 		
WEEE standards	• Directive 2002/96/EC & 2012/19/EU		

Antennas Pattern





More Information

For more information about Huawei WLAN products, visit http://e.huawei.com or contact Huawei's local sales office.

Alternatively, you can contact us through one of the following methods:

- 1. Global service hotline: http://e.huawei.com/en/service-hotline
- 2. Enterprise technical support website: https://support.huawei.com/enterprise/en/index.html
- 3. Service email address for enterprise users: support_e@huawei.com

Copyright © Huawei Technologies Co., Ltd. 2024. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei Cloud and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

HUAWEI TECHNOLOGIES CO., LTD.

Address: Huawei Industrial Base, Bantian, Longgang, Shenzhen, People's Republic of China

Post code: 518129

Website: www.huawei.com