

Huawei OptiXstar EN8010Ts-20 Datasheet

01

Huawei EN8010Ts-20, an XGS-PON bridging-type ONT

Overview

The Huawei OptiXstar EN8010Ts-20 is an XGS-PON bridging-type ONT in the Huawei all-optical access solution. It uses the XGS-PON technology to implement ultra-broadband access for users.



Device Parameters

Dimensions (H x W x D) (without pads)	32 mm x 105 mm x 110 mm	System power supply	12 V DC, 1 A
Weight	About 163 g	Static power consumption	5 W
Operating temperature	0°C to 40°C	Maximum power consumption	6 W
Operating humidity	5% RH to 95% RH (non-condensing)	NNI	XGS-PON
Power adapter input	100-240 V AC, 50/60 Hz	UNI	1*10GE
Indicators	Power/PON/LOS/10G LAN	Optical connector	SC/APC
Memory	128MB Flash, 32MB RAM	-	-

Interface Parameters

XGS-PON port	Ethernet port
<ul style="list-style-type: none"> Class N1/N2/E1 Receiver sensitivity: -28 dBm Wavelengths: US 1260-1280 nm, DS 1575-1580 nm Wavelength blocking filter (WBF) Flexible mapping between GEM Port and TCONT SN/Password/SN+Password/Bi-directional authentication based on OMCI Upstream and downstream FEC SR-DBA and NSR-DBA 9.95328 Gbit/s upstream, 9.95328 Gbit/s downstream 	<ul style="list-style-type: none"> Ethernet port-based VLAN tags and tag removal 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission QinQ VLAN Limit on the number of learned MAC addresses MAC address learning Auto-adaptive 10000Mbit/s, 5000Mbit/s, 2500Mbit/s, 1000Mbit/s, 100Mbit/s


Product Function

Smart O&M	Multicast	QoS	Common O&M
<ul style="list-style-type: none"> Variable-length OMCI messages Rogue ONT detection and isolation from the OLT PPPoE/DHCP simulation testing 	<ul style="list-style-type: none"> IGMP v2/v3 snooping MLD v1/v2 snooping Fast leave VLAN tag translation, transparent transmission, and removal for downstream multicast packets IGMP/MLD protocol packet rate limitation 	<ul style="list-style-type: none"> Ethernet port rate limitation 802.1p priority SP/WRR/SP+WRR Broadcast packet rate limitation Flow mapping based on the VLAN ID, port ID, or/and 802.1p 	<ul style="list-style-type: none"> OMCI/Web UI Dual-system software backup and rollback 802.1ag Ethernet OAM Optical link measurement and diagnosis
Security <ul style="list-style-type: none"> MAC address filtering 	Power Saving <ul style="list-style-type: none"> Indicator power saving CoC V8 	-	-

Copyright © Huawei Technologies Co., Ltd. 2023. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base Bantian, Longgang Shenzhen 518129 People's Republic of China

Website: <http://www.huawei.com>